



## FUNE IN ACCIAIO MARTELLATA

### 6 X 19S + IWRC • EN 12385-4

S = corona fili esterni del trefolo con diametro maggiore ai fili interni

IWRC = anima metallica indipendente

| CODICE<br>nr     | Ø<br>mm ca. | PESO<br>Kg/m | CARICO DI ROTTURA MIN. [MBL]<br>R1960 N/mm <sup>2</sup> • kN (1 kN = 101,97 kg) |
|------------------|-------------|--------------|---|
| FLM0800I114SE4AZ | 8           | 0,36         | 63  |
| FLM0900I114SE4AZ | 9           | 0,4          | 83  |
| FLM1000I114SE4AZ | 10          | 0,57         | 103   |
| FLM1100I114SE4AZ | 11          | 0,69         | 118   |
| FLM1200I114SE4AZ | 12          | 0,82         | 140   |
| FLM1300I114SE4AZ | 13          | 0,95         | 160   |
| FLM1400I114SE4AZ | 14          | 1,11         | 188   |
| FLM1600I114SE4AZ | 16          | 1,45         | 253   |
| FLM1800I114SE4AZ | 18          | 1,84         | 320   |
| FLM2000I114SE4AZ | 20          | 2,27         | 394   |
| FLM2200I114SE4AZ | 22          | 2,75         | 469   |
| FLM2400I114SE4AZ | 24          | 3,28         | 558   |
| FLM2600I114SE4AZ | 26          | 3,90         | 630   |

